

# PSk2-21 CS-F42-40

## Solar Surface Pump System

### System Overview

Head	max. 80 m
Flow rate	max. 63 m <sup>3</sup> /h

### Technical Data

#### Controller PSk2-21

- High efficiency solar pump controller
- Hybrid power (solar / grid / generator) support with LORENTZ SmartSolution
- Inputs for water meter, pressure sensors, digital switches
- Simple configuration with LORENTZ PumpScanner Android™ App
- Onboard data logging and system monitoring
- Inbuilt applications for constant pressure, constant flow and daily amount
- Integrated Sun Sensor
- Active temperature management
- Integrated MPPT (Maximum Power Point Tracking)

Power	max. 21 kW
Input voltage	max. 850 V
Optimum Vmp**	> 575 V
Motor current	max. 33 A
Efficiency	max. 98 %
Ambient temp.	-30...50 °C
Enclosure class	IP54

#### Motor AC DRIVE CS-F 15kW

- Highly efficient 3-phase AC motor
- Frequency: 25...51 Hz

Efficiency	max. 82 %
Motor speed	1,400...2,905 rpm
Power factor	0.87
Insulation class	F
Enclosure class	IPX4

#### Pump End PE CS-F42-40

- Premium materials
- Centrifugal pump

Efficiency	max. 85 %
------------	-----------

#### Pump Unit PUK2-21 CS-F42-40 (Motor, Pump End)

Water temperature	max. 70 °C****
Suction head	acc. to COMPASS sizing

### Standards



2006/42/EC, 2004/108/EC, 2006/95/EC

IEC/EN 61702:1995, IEC/EN 62253 Ed.1

The logos shown reflect the approvals that have been granted for this product family. Products are ordered and supplied with the approvals specific to the market requirements.

\*\*Vmp: MPP-voltage under Standard Test Conditions (STC): 1000 W/m<sup>2</sup> solar irradiance, 25 °C cell temperature

\*\*\*\*Special solutions available for >70 °C, please consult your distributor




## PSk2-21 CS-F42-40


Solar Surface Pump System

### Pump Chart

Vmp\* > 575 V



### NPSH



The NPSH (Net Positive Suction Head) is NOT the operating suction head. To calculate the operating suction head please refer to the installation manual.

\*Vmp: MPP-voltage under Standard Test Conditions (STC): 1000 W/m² solar irradiance, 25 °C cell temperature




# PSk2-21 CS-F42-40

## Solar Surface Pump System

### Dimensions and Weights


#### Controller

H = 500 mm  
 H1 = 450 mm  
 H2 = 421 mm  
 W1 = 320 mm  
 W2 = 290 mm  
 D = 9.0 mm  
 D1 = 226 mm



#### Pump Unit

A = 330 mm  
 B = 255 mm  
 C = 490 mm  
 D = 365 mm  
 E = 245 mm  
 F = 190 mm  
 G = 140 mm  
 H = 906 mm  
 I = G1/2"  
 J = 330 mm  
 K = 266 mm  
 L = 80 mm  
 M = 160 mm  
 N = 18 mm  
 O = 45 mm  
 P = 14 mm



	Net weight
Controller	18 kg
Pump Unit	197 kg
Motor	117 kg
Pump End	80 kg

